



# BEAVER TAIL TRAILER



movingforward@durahaul.com  
US toll free 844-877-6221

[www.durahaul.com](http://www.durahaul.com)



Specifications may vary by model ordered.

- » **Capacity**  
80,000 lbs GVWR
- » **Length**  
48' / 53'
- » **Weight**  
13,920 lbs +/- 3%
- » **Ramps**  
DuraRamps  
Spring assisted  
Third ramp optional
- » **Upper Deck Length**  
10' 6"
- » **Lower Deck Length**  
37' 6"
- » **Upper Deck Height**  
62"
- » **Lower Deck Height**  
41"
- » **Width**  
102" Overall
- » **Coupler Height**  
48"
- » **King Pin**  
2" Holland  
Setting 24"
- » **Plate**  
1/4"
- » **Main Beam**  
27" High Tensile Steel
- » **Web**  
Grade 80 High Tensile Steel
- » **Front Skirt**  
Formed Steel with Tapered Corners
- » **Rear Skirt**  
Formed Steel with Integral Stake Pockets
- » **Cross Members**  
4" Steel I Beam on 12" centers
- » **Side Rail**  
6" Steel Channel
- » **Rubrail**  
3/8" x 2-1/2" Steel
- » **Stake Pockets**  
Steel, External Mount, 24" on center with double pipe spools
- » **Floor**  
1-1/8" Apitong Hardwood
- » **Lighting**  
Lights Full DOT approved LED sealed lights
- » **Load Securement**  
Sliding Winch C-track
- » **Mud Flaps**  
Heavy Duty, White
- » **Suspension**  
Heavy Duty Air Ride, 25,000 lbs capacity
- » **Axles**  
Heavy Duty, 25,000 lbs capacity
- » **Landing Gear**  
Jost - Heavy Duty, 2-speed Gear Drive, 160,000 lbs static load capacity
- » **ABS Brakes**  
Bendix, 2S1M
- » **Parking Brakes all Axels**
- » **Brakes**  
16 1/2" x 7" Quick Change
- » **Hubs**  
Standard Cast, Oil lubricated, 10-stud unimount, hub piloted
- » **Brake Drums**  
Standard Cast, outboard mount
- » **Wheels**  
Hub piloted steel
- » **Tires**  
22.5"
- » **Winches (12)**
- » **Winch Track Steel Slide Driver Side**
- » **5-step painting process**
  - ✓ Sandblasting
  - ✓ Acid wash
  - ✓ Phosphate treatment
  - ✓ Heated silicone treatment
  - ✓ Powder coat finish



## HAUL WITH THE PROS.

Options, color, and design may vary from model shown.