



# FLB FLATBED



movingforward@durahaul.com  
US toll free 844-877-6221

[www.durahaul.com](http://www.durahaul.com)



Specifications may vary by model ordered.

- » **Capacity**  
80,000 lbs GVWR
- » **Length**  
48' / 53'
- » **Weight**  
48': 13,118 lbs +/- 3%  
53': 13,850 lbs +/- 3%
- » **Deck Height**  
54"
- » **Width**  
102" Overall
- » **Coupler Height**  
48"
- » **King Pin**  
2" Holland  
Setting 24" or 18"
- » **Plate**  
1/4"
- » **Main Beam**  
48: 24.5" High Tensile Steel  
53: 26.5" High Tensile Steel
- » **Web**  
Grade 80 High Tensile Steel
- » **Front Skirt**  
Formed Steel with Tapered  
Corners
- » **Concentrated Load Capacity**  
(6ft – Centered)
- » **Rear Skirt**  
Formed Steel with Integral Stake Pockets
- » **Bumper**  
4" Square safety bumper tube
- » **Cross Members**  
4" Steel I Beam on 12" centers
- » **Side Rail**  
6" Steel Channel
- » **Rubrail**  
3/8" X 2.5" steel
- » **Stake Pockets**  
Steel, External Mount, 24" on center with  
double pipe spoils
- » **Floor**  
1-1/8" Apitong Hardwood
- » **Lighting**  
Lights Full DOT approved LED sealed lights
- » **Load Securement**  
Sliding Winch C-track
- » **Mud Flaps**  
Heavy Duty, Black
- » **Landing Gear**  
Jost - Heavy Duty, 2-speed Gear Drive,  
160,000 lbs static load capacity
- » **Suspension**  
Heavy Duty Air Ride, 25,000lb Capacity
- » **Axles**  
Heavy Duty, 25,000 lbs capacity
- » **ABS Brakes**  
Wabco, 2S1M
- » **Parking Brakes all Axles**
- » **Brakes**  
16 1/2" x 7" Quick Change
- » **Hubs**  
Standard Cast, Oil lubricated, 10-stud unimount,  
hub piloted
- » **Brake Drums**  
Standard Cast, outboard mount
- » **Wheels**  
Hub piloted steel
- » **Tires**  
22.5"
- » **Winches (12)**  
48' - 12 53' - 14
- » **Winch Track Steel Slide Driver Side**
- » **Options:**
  - ✓ Spread axles
  - ✓ Closed tandem rear axles
  - ✓ Closed tandem front axles
  - ✓ Sliding axles



\*Features and specs may change at any time without notice.  
\*\*Design may vary from model shown.